

## MAGNETIC HOLDER

**Features** 


- Precision ground multi angle face holding block.
- Opposite side with Plane and V-face.
- Switching On/Off with rotating handle
  and variable power.
- Six working faces activated at a time with 45°/90°/135°, job set up facility.

| e      |   |            | -    |   |
|--------|---|------------|------|---|
| face.  | - | and an and |      |   |
| andle  |   |            | 5    |   |
| time   |   |            | -199 |   |
| ility. |   |            | /    | • |
| 1      | T | 1          |      |   |
|        |   | COLUMN D   | -    |   |

| All dimensions are in mm. |              |     |     |     |            |  |
|---------------------------|--------------|-----|-----|-----|------------|--|
| Art. No.                  | Working Face | L   | W   | Н   | Pull (Kgs) |  |
| 31113.01                  | NORMAL       | 110 | 110 | 140 | 100        |  |
| 31113.02                  | HARDENED     | 110 |     |     | 75         |  |

#### **Applications**

- Useful during measuring and marking of round work pieces and also flat pieces.
- Can hold pipes/ flat component for welding, drilling and grinding.
- Suitable for tack welding work.



# MAGNETIC VICE

#### **Features**

- Precision ground vice with flatness, parallelism and square ness within 5 Microns.
- Most suitable for use as an auxiliary tool for grinding small or tapered objects or the ends of rods and flat plates vertically up.
- Magnetic force acts from both sides in a vice-like fashion.
- The upper surface and both sides are magnetic and are thus suitable for processing work pieces that require a right angle square.

| All | All dimensions are in mm. |     |     |    |               |
|-----|---------------------------|-----|-----|----|---------------|
| A   | rt. No.                   | L   | W   | Н  | Clamping Area |
| 3   | 1114.01                   | 180 | 110 | 75 | 65 x 100      |
| 3   | 1114.02                   | 225 | 160 | 90 | 75 x 150      |

### **Applications**

- For machining applications where accuracy and holding of irregular jobs are required.
- V face of the movable jaw can be aligned to the work piece face.
- Can hold delicate jobs without distortion.

## MAGNETIC POSITIONER

### **Applications**

- For positioning of jobs at right angle.
- Round jobs can also be positioned.

#### **Features**

- Compact in Size.
- Ground accurately on all sides.
- Made with powerful everlasting Alnico magnets.

| All dimensions are in mm. |     |    |    |                 |
|---------------------------|-----|----|----|-----------------|
| Art. No.                  | L   | W  | н  | Weight<br>(Kgs) |
| 31115.01                  | 152 | 41 | 45 | 1.4             |
| 31115.02                  | 178 | 41 | 45 | 1.6             |

- Due to continuous upgradation in design there could be changes in specifications.
- Other sizes on request.